

BOXER[®] 322D

Model Specifications

Engine System

Type	Kubota D902
HP / KW	22 / 16.1
Fuel Tank	4.5 Gallons
Reservoir Capacity	16 Gallons
Hydraulic Pressure (at Attachment)	3000 psi System Relief
Hydraulic Flow	9.4 gpm
Hydraulic Flow Ground Drive	9.4 gpm
Engine Warranty	2 Years
Product Warranty	1 Year
Operator Platform	Spring Loaded
Creep Control	N/A

Units

	English	Metric
Wheel Base	32 in	813 mm
Wheel/Track Option	7 in	177.8 mm
Track Widening Undercarriage	N/A	N/A
Ground Clearance	5 in	127 mm
Length (w/Bucket)	93 in	2362 mm
Length (w/out Bucket)	68 in	1727 mm
Width (Fully Retracted)	N/A	N/A
Width (Fully Extended)	34.5 in	876 mm
Overall Height	49 in	1245 mm
Overall Operating Height (Fully Raised)	92 in	2337 mm
Hinge Pin Height (Fully Raised)	70 in	1778 mm
Dump Height	54 in	1372 mm
Dump Angle	34 Degrees	34 Degrees
Reach	28 in	711 mm
Tip Capacity	1325 lbs	601 kg
Operating Capacity, 35% of tip load.	464 lbs	210 kg
Operating Capacity, 50% of tip load.	663 lbs	301 kg
Weight (w/out Bucket)	1900 lbs	862 kg
Ground Pressure	3.3 psi	22.6 kPa
Ground Speed (Max)	3.4 mph	5.5 kph

