

6000, 7500 & 8000-Watt Gasoline

Built to work, you'll want this generator on every jobsite. Its heavy-duty full-wrap frame and impact resistant corners minimizes damage from rough handling. A performance-proven engine makes it reliable and efficient and because it's a Mi-T-M you'll enjoy using it for many years.



GEN-7500-0MHE featuring an electric start engine

Engine

- Low-oil shutdown engine
- Electric start available (battery included)
- Idle control

Alternator

- Brushless 120V/240V alternator
- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame

- Heavy-duty wraparound frame with 1-inch powder coated steel tubing
- Low profile, compact design
- Angled isolator design features four neoprene isolators

Components

- Large low-tone mufflers to reduce noise to lowest level possible
- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Fuel shut-off valve
- Easy-to-read fuel gauge
- Voltmeter/hour meter
- Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting
- Heavy-duty industrial air cleaners hold up under extreme conditions

Miscellaneous


- USDA/USFS-approved spark arrestors
- Circuit breaker protected

Warranties


2 YEAR LIMITED ALTERNATOR WARRANTY

3 YEAR LIMITED HONDA ENGINE WARRANTY

3 YEAR LIMITED SUBARU ENGINE WARRANTY



GFCI 5-20R
All Models



NEMA L14-20R
125/250V
GEN-6000
Models



NEMA L14-30R
125/250V
GEN-7500 &
8000 Models



NEMA L5-30R
125 VAC
GEN-7500 &
8000 Models



CSA
CERTIFIED

Model Number	GEN-6000-0MHO [^] / GEN-6000-0MSO [^]	GEN-7500-0MHO [^]	GEN-8000-0MSO [^]
Max. AC Output	6000 watts	7500 watts	8000 watts
Rated AC Output	5000 watts	6500 watts	6900 watts
Displacement/Engine	389cc Honda OHV / 404cc Subaru OHC	389cc Honda OHV	404cc Subaru OHC
Frequency/Voltage	60Hz/120V/240V	60Hz/120V/240V	60Hz/120V/240V
Max. Amps (120V/240V)	50.0/25.0	62.5/31.25	66.7/33.3
Cont. Amps (120V/240V)	41.7/20.8	54.2/27.1	57.5/28.75
Receptacles	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock	(2) 120V, 20A GFCI duplex 120V, 30A twist lock 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex 120V, 30A twist lock 120V/240V, 30A twist lock
Main Circuit Breakers	(2) 20A toggle circuit breaker, single pole (2) 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breaker, single pole 30A toggle circuit breaker, single pole 30A toggle circuit breaker, double pole	(2) 20A toggle circuit breaker, single pole 30A toggle circuit breaker, single pole 30A toggle circuit breaker, double pole
Rated Speed	3600 RPM	3600 RPM	3600 RPM
Decibel Rating	77.1 / 77.4	80.0	78.2
Fuel Capacity	7.3 gallons	7.3 gallons	7.3 gallons
Run Time (at full load)	8.0 hours / 7.9 hours	6.9 hours	6.9 hours
Dimensions (LxWxH)	29in.x24.4in.x22.5in.	29in.x24.4in.x22.5in.	29in.x24.4in.x22.5in.
Ship Wt.	232 lbs.	255 lbs.	245 lbs.
Net Wt.	210 lbs.	233 lbs.	223 lbs.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

[^]Available with electric start (battery included).

ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
32-0915	RV generator adapter - 30A/125V female/male; use to connect RV cordsets to 30A generators	All models
AW-5090-0004	Lifting hook - For easier portability, folds down and out of the way when not in use	All models
AW-5740-0010	Wheel kit - For easier portability, pneumatic tires with tubes, rubber gripped handles	All models
TX-1002-W	Puncture-proof tires - Tires are flat-free and maintenance-free, 10-inch, white hub, two tires	All models