



KOSHIN 2", 1 HP SUBMERSIBLE PUMP

PB7-65011

Features

- Impeller and casing are manufactured from a blended rubber compound providing maximum wear resistance, up to three times over cast iron.
- Water is channeled through the outer wall to cool the motor for maximum endurance.
- It is compact, light-weight, easy to carry and handle.
- Double mechanical seals run in an "oil" filled chamber of liquid paraffin to prevent damage from periods of dry running.
- Liquid paraffin is used in the shaft seal, therefore water will not be contaminated even in the case of oil leakage.
- The cord is of uni-body construction ensuring excellent water tightness.
- The built-in thermal protector turns off the power supply in case of overload operation thus protecting the motor.




Applications

- Construction site, excavations, well casings and general dewatering.
- Utilities, manhole and vault draining.
- Residential, draining of basements, crawl spaces and swimming pools.

Specifications

Model	PB7-65011
Discharge Size	2"
Motor Output	1 HP
Delivery Volume	89 GPM
Total Head	59 Ft.
Voltage	110 V
Rated Current	10.9 Amps
Cable Length	32 Ft.
Net Weight	42 Lbs.

Performance



KOSHIN AMERICA CORP.

1218 Remington Road • Schaumburg, IL 60173
847/884-1570 • 800/634-4092 • FAX 847/310-0740

Distributed by: