

MT100 Mini Track Loader



No need for wheelbarrows, shovels or other hand tools when you roll onto jobsites with the Bobcat® MT100 mini track loader.

- Fit through gates, doorways and other narrow spaces
- 1,000 lb. rated operating capacity
- Powerful breakout force and impressive lift height

[Build & Quote](#)[Contact Dealer](#)[View Offers](#)[Find Dealer](#)[Download Brochure](#)

MT100 Overview

- The MT100 travels through gates, doorways and other narrow spaces with ease.
- The machine also delivers a big boost in power with a 1,000-pound rated operating capacity, powerful breakout force and impressive lift height.
- The optimized roller spacing on the MT100's track system improves ride quality for enhanced operator comfort and confidence when working long days.
- Easy, tool-free access to maintenance areas and advanced safety features, including neutral start interlocks, are standard on the MT100 mini track loader, while sealed rollers eliminate the need for daily roller maintenance and decrease downtime.
- This loader also features high-flotation tracks that allow it to move across wet and muddy ground.

MT100 Specifications

MT100 Key Specifications

Rated Operating Capacity (ISO)	1,000 lb
Carry Position ROC with Standard Counterweight -UnderCarriage Position	1,300 lb
Operating Weight	3390 lb
Ground Pressure (Rubber)	5.25 psi
Auxiliary Std Flow	12 gal/min
Width	35.6 in
Height to Bucket Hinge Pin	80.9 in

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	55 in ³
Number of Cylinders	3
Horsepower	24.8 hp

Performance

Rated Operating Capacity (ISO)	1,000 lb
Carry Position ROC with Standard Counterweight -UnderCarriage Position	1,300 lb
Tipping Load	2898 lb
Operating Weight	3390 lb
Ground Pressure (Rubber)	5.25 psi

Travel Speed	4.1 mph
Travel Speed - Reverse	2.9 mph

Capacities

Fuel Tank	7 gal
-----------	-------

Hydraulic System

Pump Capacity	12 gal/min
System Relief @ Quick Couplers	2,900 psi
Auxiliary Std Flow	12 gal/min

Dimension

Length	106.2 in
Width	35.6 in
Height	54.6 in
Height to Bucket Hinge Pin	80.9 in
Length of track on ground	41.4 in
Reach @ Maximum Height	18.6 in

Features

Lift-Arm Support	Standard
Auxiliary Hydraulics	Standard
Spark Arrestor Muffler	Standard
Bob-Tach Attachment System	Standard
Reverse Travel Stop Panel	Not Applicable
Wide Track	Optional
Neutral Start Interlocks	Standard
Lift Arm Lockout With Manual Bypass	Standard
Tilt Lockout	Standard
Built-In Tie Down & Crane/Lift Locations	Standard
Ride-on Platform	Standard

MT100 Features & Benefits

[Expand all](#)

Performance ⁵

Versatility ³

Comfort ⁴

Serviceability ²

MT100 Attachments

[View All Attachments](#)



WARNING: This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.