

**DIESEL
POWERED ENGINE**

X-SMART

4X320W LED - 26'

Designed to provide
an exceptional level
of performance
for every jobsite
ensuring the right
balance between
power and ease of use

LED TECHNOLOGY

52,900 sq ft
Illuminated area

288 hr
run time



creating a
more sustainable
and environmentally
friendly future

TRIMEUSA

X-SMART

4x320W - LED - 26'

LED TECHNOLOGY

52,900 sq ft

Illuminated area

RUN TIME
46 gal tank
288hrs

NOISE
level @ 23' - 65 dBA

Dusk to Dawn control

APPLICATIONS



Construction
& work sites



Gas, oil & mining
operations



Emergency



Events



Military

FEATURES

- ✓ Full run time 288 hrs - that's almost a full month of darkness on one tank of diesel! Refuel once a month versus five times a month with metal halide towers. Save on fuel and labor refueling costs!
- ✓ 4 x 320W high efficiency LED light heads have a 5-year warranty and are easily tilted & rotated by hand, illuminating a 52,900 sq ft area.
- ✓ Kubota Z482-E4B engine with 1,000 hour service intervals
- ✓ Hydraulically operated vertical mast fully raises in 10 sec. with the push of a button with 26' maximum height.
- ✓ Set the timer and go! No need to send labor to start every night. Use programmable event timer or dusk to dawn switch. Save time and money!
- ✓ Built for a long life! Rugged 14 gauge steel enclosure and fenders are galvanized and powder coated inside and out. Documented towers with 40,000+ hours.
- ✓ 110% containment base



DIESEL POWERED ENGINE



Mast - Dimensions & Weight

Mast Height	26'
Wind Rating	50 mph
Fully Retractable Stabilizers	Y
Axle	Torsion
Drawbar	Tubular Steel
Unit Dimensions - Stowed	95"l x 57" w x 98" h
Operating Dimensions	95"l x 107" w x 315" h
Dry Weight	1964 lbs
Operating Weight	2270 lbs

Engine

Make - Model	Kubota - Z482-E4B
Make - Model	Kohler - KDW702
Emission Regulation	Tier 4
Type	Vertical 4 Cycle Liquid Cooling Diesel
Cylinder	2
Displacement / L (cu. In.)	0.479 (29.23)
Combustion System	IDI
Intake System	Naturally Aspirated
Maximum Speed	1800 rpm
Sound Level @ 23'	65 dBA

Alternator

Make	Linz
Output	4.2 kVA
Hz	60

Fuel

Type	Diesel
Fuel Capacity	46 gal.
Run Time	288 Hrs

Secondary Containment

Containment Base	110%
------------------	------

Options

Anti-Glare Lights
Wildlife-Safe Lights
Skid Mount
Off-Road Receiver Hitch
Customized Telematics



Trime US, Inc. - 3 Killdeer Court, Suite 301 - Swedesboro, NJ 08085 - www.trimeusa.com
(877) 97TRIME - (877) 978-7463 - sales@trimeusa.com

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.